



HIGH PERFORMANCE
TRAILER TYRES



HAPPYROAD

JUMBO
GRANDSTONE
MASTERTYRES



Y206 HAPPYROAD



- Wide tread design ensure excellent wear-resistance
- It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handing
- The tread of the has middle winding groove desing offering excellent road grabbing performance to ensure safety
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12R22.5	18	9.00	15.5	300	1085	930	930	3550	3250
12R22.5	16	9.00	15.5	300	1085	830	830	3350	3075



Y216 HAPPYROAD



- Wide tread design ensure excellent wear-resistance
- It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handing
- The tiny deep-groove pattern design of the side of tread that can improve the ability of avoiding partial grinding
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	14.5	279	1054	830	830	3000	2725
11R22.5	14	8.25	14.5	279	1054	720	720	2800	2650
295/80R22.5	18	9.00	14.5	298	1044	900	900	3550	3250
295/80R22.5	16	9.00	14.5	298	1044	830	830	3350	3075
315/80R22.5	18	9.00	14.5	312	1076	830	830	3750	3450
315/80R22.5	16	9.00	14.5	312	1076	760	760	3450	3150



Y226 HAPPYROAD



- Wide tread design ensure excellent wear-resistance
- It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handing
- The tiny deep-groove pattern design of the side of tread that can improve the ability of avoiding partial grinding
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
295/80R22.5	18	9.00	14.5	298	1044	900	900	3550	3250
295/80R22.5	16	9.00	14.5	298	1044	830	830	3350	3075
315/70R22.5	16	9.00	14.5	312	1014	760	760	3250	3000
315/70R22.5	18	9.00	14.5	312	1014	830	830	3450	3150
11R22.5	16	8.25	14.5	279	1054	830	830	3000	2725
11R24.5	16	8.25	14.5	279	1104	830	830	3250	3000
295/75R22.5	16	9.00	14.5	298	1014	830	830	3000	2725
385/65R22.5	20	11.75	15.5	389	1072	900	900	4500	4500



GT178 GRANDSTONE



- Wide tread design ensure excellent wear-resistance
- It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handing
- The tread of the has middle winding groove desing offering excellent road grabbing performance to ensure safety
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	14.5	279	1054	830	830	3000	2725
11R24.5	16	8.25	14.5	279	1104	830	830	3250	3000
295/75R22.5	16	9.00	14.5	298	1014	830	830	3000	2725



M216 MASTERTYRES



- Wide tread design ensure excellent wear-resistance
- It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handing
- The tiny deep-groove pattern design of the side of tread that can improve the ability of avoiding partial grinding
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	14.5	279	1054	830	830	3000	2725
11R22.5	14	8.25	14.5	279	1054	720	720	2800	2650
295/80R22.5	18	9.00	14.5	298	1044	900	900	3550	3250
295/80R22.5	16	9.00	14.5	298	1044	830	830	3350	3075
315/80R22.5	18	9.00	14.5	312	1076	830	830	3750	3450
315/80R22.5	16	9.00	14.5	312	1076	760	760	3450	3150



SS618 JUMBO



- Wide tread design ensure excellent wear-resistance
- It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handing
- The tiny deep-groove pattern design of the side of tread that can improve the ability of avoiding partial grinding
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
295/80R22.5	18	9.00	14.5	298	1044	900	900	3550	3250
295/80R22.5	16	9.00	14.5	298	1044	830	830	3350	3075
315/70R22.5	16	9.00	14.5	312	1014	760	760	3250	3000
315/70R22.5	18	9.00	14.5	312	1014	830	830	3450	3150
11R22.5	16	8.25	14.5	279	1054	830	830	3000	2725
11R24.5	16	8.25	14.5	279	1104	830	830	3250	3000
295/75R22.5	16	9.00	14.5	298	1014	830	830	3000	2725
385/65R22.5	20	11.75	15.5	389	1072	900	900	4500	4500



Y236 HAPPYROAD



- Due to the design of 5 ribs thread, the guiding and controlling of the tyre has been enhanced
- High performance when driving on slippery
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
315/80R22.5	18	9.00	16	312	1076	830	930	3750	3450
315/80R22.5	20	9.00	16	312	1176	875	830	4000	3350



Y256 HAPPYROAD



- High wear resistance and eccentric wear resistance. Good heat release capacity
- Excellent controllability performance
- Avoid champing stones
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12R22.5	18PR	9.00	17	296	1085	930	930	3550	3250



Y706 HAPPYROAD



- This tire has good performance of draining and driving and it also has excellent wear-resistance driving power and braking ability
- It has marvelous braking ability, turning ability and safety assurance
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	16.5	279	1054	830	830	3000	2725
11R22.5	14	8.25	16.5	279	1054	720	720	2800	2650
295/80R22.5	18	9.00	17	298	1044	900	900	3550	3250
295/80R22.5	16	9.00	17	298	1044	830	830	3350	3075
315/80R22.5	18	9.00	18	312	1076	830	830	3750	3450
315/80R22.5	16	9.00	18	312	1076	760	760	3450	3150



Y709/Y709+ HAPPYROAD



- The tire has broad tread pattern block, and deep pattern design that offering strong power
- The tire uses strong structure that owns good carrying capability
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12.00R20	18	8.5	24.5	315	1125	830	830	3750	3450
12.00R20	20	8.5	24.5	315	1125	900	900	4000	3650
11.00R20	18	8.0	22.5	293	1085	930	930	3550	3250
11.00R20	16	8.0	22.5	293	1085	830	830	3550	3075



Y716 HAPPYROAD



- The tire has the design that can balance the inner contour which vastly improve the endurance quality of the belt
- The new formula of the tire tread is especially developed, which can efficiently reduce the hot generation and offer a good performance of wear-resistance
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	18	279	1054	830	830	3000	2725
11R22.5	14	8.25	18	279	1054	720	720	2800	2650
295/80R22.5	18	9.00	18	298	1044	900	900	3550	3250
295/80R22.5	16	9.00	18	298	1044	830	830	3350	3075
315/80R22.5	18	9.00	18	312	1076	830	830	3750	3450
315/80R22.5	16	9.00	18	312	1076	760	760	3450	3150



Y726 HAPPYROAD



- Special block pattern ensure the excellent braking and driving ability. Outstanging road grasping capcity
- Deep groove design and good wear-resistance compound ensures long service life
- Good anti-shock function and heat dispersion performance
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12R22.5	18	9.00	20	300	1085	930	930	3550	3250
12R22.5	16	9.00	20	300	1085	830	830	3350	3075
315/80R22.5	16	9.00	20	312	1076	830	830	3750	3450
315/80R22.5	18	9.00	20	312	1076	760	760	3450	3150



Y746 HAPPYROAD



- The small pieces of middle lateral patterns offer good braking, driving and grip performance
- The design of the closed shoulder pattern good wear resistance and balance abrasion
- Excellent comprehensive performance comes from special formula of low thermogenesis and good wear resistance
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	20	279	1054	830	830	3000	2725
11R24.5	16	8.25	20	279	1104	830	830	3250	3000
295/75R22.5	16	9.00	20	298	1014	830	830	3000	2725



Y756 HAPPYROAD



- Mixing rib tread with deep depth ensures good driver capacity
- Good self cleaning ability
- Excellent driving performance
- Applied with anti cutting and puncture compound
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12R22.5	18PR	9.00	20	296	1085	930	930	3550	3250



Y778 HAPPYROAD



- The special designed tread pattern ensures good grip strength
- Its deep pattern ensures longer tire life
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12R22.5	18PR	9.00	20	296	1085	930	930	3550	3250



GT238 GRANDSTONE



- The small pieces of middle lateral patterns offer good braking, driving and grip performance
- The design of the closed shoulder pattern good wear resistance and balance abrasion
- Excellent comprehensive performance comes from special formula of low thermogenesis and good wear resistance
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	20	279	1054	830	830	3000	2725
11R24.5	16	8.25	20	279	1104	830	830	3250	3000
295/75R22.5	16	9.00	20	298	1014	830	830	3000	2725



ADM678 JUMBO



- The small pieces of middle lateral patterns offer good braking, driving and grip performance
- The design of the closed shoulder pattern good wear resistance and balance abrasion
- Excellent comprehensive performance comes from special formula of low thermogenesis and good wear resistance
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	20	279	1054	830	830	3000	2725
11R24.5	16	8.25	20	279	1104	830	830	3250	3000
295/75R22.5	16	9.00	20	298	1014	830	830	3000	2725



Y736/Y736+ HAPPYROAD



- The special designed tread pattern ensures good grip strength
- Its deep pattern ensures longer tire life
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12.00R20	18	8.5	20	315	1125	830	830	3750	3450
12.00R20	20	8.5	20	315	1125	900	900	4000	3650
11.00R20	18	8.0	18.5	293	1085	930	930	3550	3250
11.00R20	16	8.0	18.5	293	1085	830	830	3350	3075
10.00R20	18	7.5	17	278	1054	930	930	3250	3000
10.00R20	16	7.5	17	278	1054	830	830	3000	2725
9.00R20	16	7.0	16	259	1019	900	900	2800	2650
9.00R20	14	7.0	16	259	1019	790	790	2575	2430
12R22.5	18	9.00	18	300	1085	930	930	3550	3250
12R22.5	16	9.00	18	300	1085	830	830	3350	3075
11R22.5	16	8.25	17	279	1054	830	830	3000	2725



Y326 HAPPYROAD



- The tire has three-groove and siping pattern design that has great adhesion property
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	14.5	279	1054	830	830	3000	2725
11R22.5	14	8.25	14.5	279	1054	720	720	2800	2650
295/80R22.5	18	9.00	14.5	298	1044	900	900	3550	3250
295/80R22.5	16	9.00	14.5	298	1044	830	830	3350	3075
315/80R22.5	18	9.00	16	312	1076	830	830	3750	3450
315/80R22.5	16	9.00	16	312	1076	760	760	3450	3150
12R22.5	18	9.00	16	300	1085	930	930	3550	3250
12R22.5	16	9.00	16	300	1085	830	830	3350	3075



Y336 HAPPYROAD



- Due to the design of 3 ribs thread, the guiding and controlling of the tyre has been enhanced
- The small pieces of middle lateral patterns offer good braking, driving and grip performance
- The design of the closed shoulder pattern offers good wear resistance and balance abrasion good wear resistance

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12.00R24	20	8.5	15	315	1226	900	900	4500	4125



Y506 HAPPYROAD



- Excellent anti-damage ability can undertake complex road conditions
- Fit for trailer axle of the trailers and suitable for complex road conditions
- High strength tyre carcass is suitable for retreading

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	SINGLE-TYRE		
385/65R22.5	20	11.75	15.5	389	1072	900		4500	



Y306 HAPPYROAD



- Classic pattern with three groove design ensure small rolling and low heat generation
- Ensure driving comfortable and safety during operation
- Low running noise
- General wheel position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
13R22.5	18	9.75	15.5	320	1124	830	830	3750	3450
12R22.5	18	9.00	15.5	300	1085	930	930	3550	3250
12R22.5	16	9.00	15.5	300	1085	830	830	3350	3075
315/80R22.5	18	9.00	16	312	1076	830	830	3750	3450
315/80R22.5	20	9.00	16	312	1076	900	900	4125	3750
12.00R24	18	8.5	15	315	1226	830	830	4250	3850
12.00R24	20	8.5	15	315	1226	900	900	4500	4125
12.00R20	18	8.5	16.5	315	1125	830	830	3750	3450
12.00R20	20	8.5	16.5	315	1125	900	900	4000	3650
11.00R20	18	8.0	16	293	1085	930	930	3550	3250
11.00R20	16	8.0	16	293	1085	830	830	3350	3075
10.0R20	18	7.5	16	278	1054	930	930	3250	3000
10.0R20	16	7.5	16	278	1054	830	830	3000	2725
9.0R20	16	7.5	15.5	259	1019	900	900	2800	2650
9.0R20	14	7.5	15.5	259	1019	790	790	2575	2430



Y316 HAPPYROAD



- Suitable for all wheel position of the trailers running on good road, distance in all various road in good condition
- Wide tread design makes long service life

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
13R22.5	18	9.75	16	320	1124	830	830	3750	3450
12R22.5	18	9.00	16	300	1085	930	930	3550	3250
12.00R20	18	8.5	16.5	315	1125	830	830	3750	3450
12.00R20	20	8.5	16.5	315	1125	900	900	4000	3650
11.00R20	18	8.0	16	293	1085	930	930	3550	3250
11.00R20	16	8.0	16	293	1085	830	830	3350	3075
10.00R20	18	7.5	16	278	1054	930	930	3250	3000
10.00R20	16	7.5	16	278	1054	830	830	3000	2725
9.00R20	16	7.0	15.5	259	1019	900	900	2800	2650
9.00R20	14	7.0	15.5	259	1019	790	790	2575	2430



Y318 HAPPYROAD



- The tire has big block mixed and deep pattern that has a wider running surface
- It has stronger traction performance and grassping ability
- The tire has great structure that owns good carrying capability
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12.00R20	18	8.5	20	315	1125	830	830	3750	3450
12.00R20	20	8.5	20	315	1125	900	900	4000	3650



Y328 HAPPYROAD



- The tread pattern is specially designed to have a stronger holding power
- Its deep pattern ensure the tire a longer service life
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12.00R20	18	8.5	21	315	1125	830	830	3750	3450
12.00R20	20	8.5	21	315	1125	900	900	4000	3650
11.00R20	18	8.0	19.5	293	1085	930	930	3550	3250
11.00R20	16	8.0	19.5	293	1085	830	830	3350	3075
10.00R20	18	7.5	17	278	1054	930	930	3250	3000
10.00R20	16	7.5	17	278	1054	830	830	3000	2725
9.00R20	16	7.0	16	259	1019	900	900	2800	2650
9.00R20	14	7.0	16	259	1019	790	790	2575	2430





Y516 HAPPYROAD



- Suitable for all wheels position of the trailers working on complex roads in all-weather conditions
- Low rolling resistance, low heat resistance, fuel economy, and excellent guiding performance
- Wide base section design offers superior and ride comfort

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
385/65R22.5	20	11.75	15.5	389	1072	900		4500	



Y308 HAPPYROAD



- The brand-new tread low heat generation compound offers extraordinary wear-resistance
- Great road grabbing performance and special anti-stones pattern design
- Its wide tread design effectively increased the volume wear that makes the service life longer
- Suitable for mounting in transimission position, only fit for tractor and semi-trailer

TYRE SIZE	PLY RATING	RIM	TREAD DEPHT (mm)	NEW TYRE INFLATION (mm)		INFLATION PRESSURE (mm)		MAXIMUM LOAD (Kg)	
				SECTION WIDTH	OVERALL DIAMETER	SINGLE-TYRE	DOUBLE-TYRE	SINGLE-TYRE	DOUBLE-TYRE
12.00R20	18	8.5	20	315	1125	830	830	3750	3450
12.00R20	20	8.5	20	315	1125	900	900	4000	3650
11.00R20	18	8.0	18.5	293	1085	930	930	3550	3250
11.00R20	16	8.0	18.5	293	1085	830	830	3350	3075
10.00R20	18	7.5	17	278	1054	930	930	3250	3000
10.00R20	16	7.5	17	278	1054	830	830	3000	2725
9.00R20	16	7.0	16	259	1019	900	900	2800	2650
9.00R20	14	7.0	16	259	1019	790	790	2575	2430





SHANDONG YUANFENG RUBBER TECHNOLOGY CO., LTD

Number 3888 in the Ze An Avenue, Gaomi, Shandong

(At the south of Liuhe Avenue and Avenue intersection east 500 meter)

Tel: 86-0536-2611111

Email: yfxkj@163.com

www.happyroadtyre.com